



# TECHNICAL DATA SHEET

## THIXOTROPIC

### COMPOSITION

25% + 1% White cement  
Portland type CEM I  
52,5 R UNE 197-1

70% + 1% of selected  
aggregates.

5% of additives.

### COLOUR RANGE

Ivory.

### SUBSTRATES

Prefabricated cement  
blocks, ceramic bricks and  
concrete.

### CONSERVATION

Store in a dry place.

### STORAGE

Shelf life is approximately  
12 months from date of  
manufacture if stored in  
unopened original packing  
in dry conditions.

### PACKAGING

25 kgs. 3 ply paper-plastic-  
paper sacks.

Shrink-wrapped pallets of  
1.400 kg.(56 sacks)

### DESCRIPTION

A mortar made from cement, selected aggregates and additives ready to be mixed with water, for manual or machine application.

For decorating façades and interiors giving a finish that imitates stone, aged brick, ashlar, wood, etc.

### HOW TO USE

Mix the product with 26% water until a homogenous blend is achieved. Wait for several minutes before applying.

Apply, manually or mechanically, a minimum thickness of 8 to 10 mm of mortar to the base using a steel trowel. Then apply DECLAFLOW (release agent) and place the mold onto the mortar, applying a light pressure until the required texture is achieved. If desired, ACOTEL (finishing pigmentation) can be applied to achieve an imitation of natural stone, aged brick, ashlar, etc. Finally apply a layer of IMPER (D or W) finishing liquid.

### CHARACTERISTICS

Thixotropic is presented in powder for its application in a paste format, allowing a thickness between 2 and 5 cm, so that it can be textured in a period of time between 4 and 8 hours, forming thematic drawings and textures through the use of sharp steel tools, cutters, scrapers and other kinds of complementary techniques provided by artist depending on the required task.

### PRECAUTIONS

The base should be clean, free of loose parts, paints and grease.  
DO NOT APPLY ONTO PLASTER.

Do not apply at temperatures below +5° C or above +35° C.

The product must not be applied to frozen or thawing supports. If the coating must be applied in adverse weather conditions, it is essential to protect both the working area and finish before and after application.

For further information consult Material Safety Data Sheet (MSDS)