



GLOXER C1E YESO

DECLARATION OF PERFORMANCE

In accordance with the European Construction Products Regulation (RPC) nº 305/2011

DoP No. ES-TC0013

1. *Name and/or Identification code of the product;*

GLOXER C1E YESO

2. *Type, lot, serial number or any type of element that let identify the construction product according to article 11, section 4:*

Cementitious adhesive. Type C1E (UNE EN 12004:2017). See the name, batch and date of manufacture on the packaging.

3. *Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as established by the manufacturer:*

Intended for the placement of ceramic wall tiles indoors and outdoors.

4. *Registered name or Brand and contact address of the manufacturer as provided for in article 11, section 5.*

ATLANTIC MORTAR S.L.
St/ Budapest, parcela 43
Polígono Industrial Cabezo Beaza
Postal code: 30353 Cartagena (Murcia)

atlantic@atlanticmortar.com

5. *Where appropriate, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12, section 2:*

Not applicable

6. *System of systems for evaluating and verifying the performance constancy of the product, as set out in annex V:*

System 3

7. *In the event of a declaration of performance relating to a construction product covered by a harmonized standard: UNE-EN 12004:2017.*

Name and identification number of the notified body: APPLUS-LGAI Technological Center S.A., identified company with number 0370.

Task performed: Initial type tests

Evaluation system: 3

Document issued: Essay report number: 11/3883-2767



GLOXER C1E YESO

8. In the case of a performance declaration relating to a construction product for which a European technical assessment has been issued::

Not applicable

9. Declared performance:

	Value	Rule
Initial adherence	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.2
Adhesion after immersion in water	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.3
Adhesion after heat aging	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.4
Adhesion after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1348 8.5
Open time (adhesion at 30 min.)	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1346
Open time (adhesión at 20 min.)	$\geq 0,5 \text{ N/mm}^2$	UNE EN-1346

When by virtue of articles 37 or 38 the specific technical documentation has been used, requirements that the product meets:


Not applicable

10. The performance of the product identified in points 1 and 2 is in accordance with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



**ATLANTIC MORTAR S.L.**
B30896252
Calle Budapest 43
Pol. Ind. Cabezo Beaza
30353 Cartagena (Spain)
Apdo. Correos 2192

Miguel Fernández Meca, technical director

Cartagena, 16-Marzo-2021