

GLOXER C2TE FLEXIBLE

DECLARATION OF PERFORMANCE

In accordance with the European Construction Products Regulation (RPC) no 305/2011

DoP No. ES-TC0014

1. Name and/or Identification code of the product:

GLOXER C2TE FLEXIBLE

2. Type, lot, serial number or any type of element that let identify the construction product according to article 11, section 4:

Cementitious adhesive. Tipo C2TE (UNE EN 12004:2017) See the name, batch and date of manufacture on the packaging.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as established by the manufacturer:

Flexible cementitious adhesive for laying ceramic wall tiles and interior and exterior floors of all types of ceramics. Especially suitable for floors with underfloor heating, skirting boards and for laying new flooring over existing flooring.

 Registered name or Brand and contact address of the manufacturer as provided for in article 11, section 5.

ATLANTIC MORTAR S.L. St/ Budapest, parcela 43 Polígono Industrial Cabezo Beaza

Postal code: 30353 Cartagena (Murcia)

atlantic@atlanticmortar.com

5. Where appropriate, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12, section 2:

Not applicable

6. System of systems for evaluating and verifying the performance constancy of the product, as set out in annex V:

System 3

7. In the event of a declaration of performance relating to a construction product covered by a harmonized standard: C2TE (UNE-EN 12004:2017)

Name and identification number of the notified body: APPLUS-LGAI Technological Center S.A., identified company with number 0370.

Task performed: Initial type tests

Evaluation system: 3

Document issued: Essay report number: 11/3883-2767

adhesive mortars



GLOXER C2TE FLEXIBLE

8. In the case of a performance declaration relating to a construction product for which a European technical assessment has been issued:

Not applicable

9. Declared performance:

| | Value | Rule |
|-----------------------------------|-----------------------|-----------------|
| Initial adhesion | ≥ 1 N/mm² | UNE EN-1348 8.2 |
| Adhesion after immersion in water | ≥ 1 N/mm ² | UNE EN-1348 8.3 |
| Adhesion after heat aging | ≥ 1 N/mm ² | UNE EN-1348 8.4 |
| Adhesion after freeze-thaw cycles | ≥ 1 N/mm ² | UNE EN-1348 8.5 |

When by virtue of articles 37 or 38 the specific technical documentation has been used, requirements that the product meets:

Not applicable

10. The performance of the product identified in points 1 and 2 is in accordance with the declared performance in point 9.

This declaration of performance is issued under the sole responsability of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:





Cartagena, 16-Marzo-2021