



PIEDRA

## DECLARATION OF PERFORMANCE

In accordance with the European Construction Products (RPC) nº 305/2011

DoP No. ES-TP0001

1. *Name and/or Identification code of the product:*

PIEDRA

2. *Type, lot, serial number or any type of element that let identify the construction product according to article 11, section 4:*

Mortar for plaster monolayer type **OC – CS II – W1**. See the name, batch and date of manufacture on the packaging.

3. *Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as established by the manufacturer:*

For waterproofing and decoration of facades and interiors. For decoration with projected aggregate in an imitation granite finish.

4. *Registered name or Brand and contact address of the manufacturer as provided for in article 11, section 5*

ATLANTIC

C/ Budapest, parcela 43  
Polígono Industrial Cabezo Beaza  
CP 30353 Cartagena (Murcia)

atlantic@atlanticmortar.com

5. *Where appropriate, name and contact address of the authorized representative whose mandate covers the tasks specified in article 12, section 2:*

Not applicable

6. *System of systems for evaluating and verifying the performance constancy of the product, as set out in annex V:*

System 3

7. *In the event of a declaration of performance relating to a construction product covered by a harmonized standard: UNE-EN 998-1:2018*

*Name and identification number of the notified body:* Centro de Estudios de Materiales y Control de Obra S.A. (CEMOSA) identified company with number 1377.

*Task performed:* Initial type tests

*Evaluation system:* 3

*Document issued:* Essay report number: 1/2831/001/014



PIEDRA

8. In the case of a performance declaration relating to a construction product for which a European technical assessment has been issued:

Not applicable

9. Declared performance:

	Value	Rule
Reaction to fire	A1(not combustible)	UNE-EN 13501-1:2002
Adhesion	0,4 N/mm <sup>2</sup> – FP:B	UNE-EN 1015-21:2003
Flexural strength	1,4 N/mm <sup>2</sup>	UNE-EN 1015-11:2000
Compressive strength	3,1 N/mm <sup>2</sup>	UNE-EN 1015-11:2000
Capillary coefficient	0,32 Kg/m <sup>2</sup> *min <sup>0.5</sup>	UNE-EN 1015-18:2003
Water vapor permeability	μ 11,84	UNE-EN 1015-19:1999
Water permeability	0,9 ml/cm <sup>2</sup>	UNE-EN 1015-21:2003
Dry bulk density	1099 Kg/m <sup>3</sup>	UNE-EN 1015-10:2000

When by virtue of articles 37 or 38 the specific technical documentation has been used, requirements that the product meets:

Not applicable

10. The performance of the product identified in points 1 and 2 is in accordance with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



 ATLANTIC MORTAR S.L.  
B30896252  
Calle Budapest 43  
Pol. Ind. Cabezo Beaza  
30353 Cartagena (Spain)  
Apdo. Correos 2192

Miguel Fernández Meca, technical director

Cartagena, 16-Marzo-2021